

Country of Origin	Import Conditions
Indonesia	<p>Require import permit and phytosanitary certificate, confirming that.</p> <ol style="list-style-type: none"> 1. Wood is fumigated using methyl bromide at the following rate: <ul style="list-style-type: none"> • 21°C and above 48 g for 24 hours • -20°C 56g for 24 hours • 11-15°C 64g for 24 hours <p>OR</p> <ol style="list-style-type: none"> 2. Heat or Kiln Drying. <ol style="list-style-type: none"> i. Less than 200mm: Dry bulb temperature at the chamber is maintained or above 74°C (165°F). Maximum thickness of timber (mm) - Duration of treatment (hours) <ul style="list-style-type: none"> • 0 to 25mm for 4 hours • 26 to 50mm for 6 hours • 51 to 75mm for 8 hours • 76 to 100mm for 10 hours • 101 to 150mm for 14 hours • 151 to 200mm for 18 hours ii. Greater than 200mm: Once a core temperature of 74°C (165°F) has been achieved, treatment duration must exceed 18 hours. Treatment time does not commence until the temperature and humidity in the chamber have stabilised and the core temperature of the timber has reached at least 74°C (165°F). All door frames must have an average moisture contain of less than 20%, based on oven-dry weight or mass. <p>Door frames are subject to inspection upon arrival. If any pest or contamination is intercepted/detected during inspection, the consignment will be detained for treatment (fumigation) at the port of entry prior to release.</p>